



PRODUCT DATA

Volumetric Ratio _____ Single Component
Solids _____ 25% (+ or - 1%)
Coverage. _____ 250-300 SQ ft/gal
Application _____ Slab
Temperature _____ 55-90°F
Color _____ Clear
Thinning _____ Not Required

CURE TIME

Dry to Touch _____ 1-2 hours
Recoat _____ 2-4 hours
Light Traffic _____ 12-24 hours
Full Cure _____ 24 - 48 hours

CONTACT

PHONE _____ (425)888-5565
WEBSITE _____ www.diygaragefloors.com
EMAIL _____ info@diygaragefloors.com



PRODUCT DESCRIPTION

DIY GARAGE FLOORS DGF-500 Acrylic Sealer is formulated with aliphatic polymers using fast drying solvents. It provides an excellent adhesion to a variety of concrete and paver surfaces. DIY GARAGE FLOORS DGF-500 Acrylic Sealer is low VOC, resistant to water stains, chemicals, salt damage, oil and grease. DIY GARAGE FLOORS DGF-500 Acrylic Sealer is highly UV stable and enhances dull or faded concrete and pavers. It seals and protects decorative concrete, stamped concrete, overlaid concrete, brick, pavers, exposed aggregate, driveways, sidewalks, walkways, porches, steps, pool decking, patios, etc. It can be applied with a roller and sprayer. It is self-priming, easy to re-coat and low maintenance. Multiple coats will increase the gloss to desired level.

APPLICATIONS

Driveways, walkways, pool decks, patios, garage floors, warehouse, exposed aggregate, some natural stone, basement floors, stamped concrete, concrete bricks, pavers, retail and restaurant floors.

ADVANTAGES

- Excellent adhesion to a variety of concrete and paver surfaces
- Low VOC
- Resistant to water, stains, chemicals, and salt damage
- Highly UV stable
- Superior color enhancement
- Seals and protects decorative concrete, stamped concrete, overlaid concrete, brick pavers, exposed aggregate, driveways, sidewalks, walkways, porches, steps, pool decking and patios
- Can be applied with a roller or sprayer

APPLICATION INSTRUCTIONS

DIY GARAGE FLOORS DGF-500 Acrylic Sealer may be applied by a brush, roller, lamb's wool applicator or industrial sprayer. Avoid any excessive buildup or puddling of product. DIY GARAGE FLOORS DGF-500 Acrylic Sealer may be applied in multiple coats to achieve desired degree of protection and gloss.

PHYSICAL PROPERTIES

Boiling Point	Over 285 degree F
Evaporation Rate	Less than 1 (n-Butyl Acetate = 1)
% Volatile by Weight	38 - 49 (Theoretical)
Vapor Density	Not Determined



PRODUCT DATA

Volumetric Ratio _____ Single Component
Solids _____ 25% (+ or - 1%)
Coverage _____ 250-300 SQ ft/gal
Application _____ Slab
Temperature _____ 55-90°F
Color _____ Clear
Thinning _____ Not Required

CURE TIME

Dry to Touch _____ 1-2 hours
Recoat _____ 2-4 hours
Light Traffic _____ 12-24 hours
Full Cure _____ 24 - 48 hours

CONTACT

PHONE _____ (425)888-5565
WEBSITE _____ www.diygaragefloors.com
EMAIL _____ info@diygaragefloors.com



HAZARDOUS COMPONENTS

Component	CAS#	% by Weight	Vapor Pressure
Mineral Spirits	64742-47-8	14 - 18	2.60
Light Aromatic Naphtha	64742-95-6	16 - 24	Less 10.0 @ 25 degree C
Proprietary Solvent, VOC exempt	98-56-6	7 - 11	N/A

COVERAGE

Approximately 250 – 300 sq. ft. per gallon, depending on substrate and application method.

Note: Test a small area before applying. NEVER THIN MORE THAN 10% BY VOLUME USING ACETONE!

CONCRETE PREPARATION

Surfaces to be sealed must be clean, dry, and free of oil, stains and silicone compounds. Do not apply DIY Acrylic Sealer until all traces of curing compounds have been completely dissipated. Substrate to be coated must be moisture free. Dries to touch in 30 minutes and may be opened to normal traffic after 4 hours, heavy traffic after 24 hours. Do not apply if air temperature and/or temperature of substrate is less than 50 degrees or higher than 90 degrees /f/, Excellent for use over colored concrete, expect a slight color change. DIY Acrylic Sealer will enhance colors. Always do a panel for approval. **DISARM ALL SPRINKLER SYSTEMS 48 HOURS PRIOR TO APPLICATION AND DURING CURE TIME.**

CLEAN UP

Equipment should be immediately cleaned with Acetone.

SAFETY

Use only in well ventilated areas. Always use gloves, protective eyewear and clothing. Overexposure to this product may cause SERIOUS HEALTH RISKS. If ingested do not induce vomiting, call a physician immediately.



PRODUCT DATA

Volumetric Ratio _____ Single Component
Solids _____ 25% (+ or - 1%)
Coverage _____ 250-300 SQ ft/gal
Application _____ Slab
Temperature _____ 55-90°F
Color _____ Clear
Thinning _____ Not Required

CURE TIME

Dry to Touch _____ 1-2 hours
Recoat _____ 2-4 hours
Light Traffic _____ 12-24 hours
Full Cure _____ 24 - 48 hours

CONTACT

PHONE _____ (425)888-5565
WEBSITE _____ www.diygaragefloors.com
EMAIL _____ info@diygaragefloors.com



WARRANTY

DIY GARAGE FLOORS products are warranted for 30 days after date of purchase. Please refer to the limited Material Warranty for additional clarification.

Disclaimer: All DIY GARAGE FLOORS products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control.

HANDLING PRECAUTIONS

Use only with adequate ventilation. Appropriate cartridge-type respirator must be used during application in confined areas. Avoid contact with skin; wear protective gloves. Read Material Safety Data Sheet before using.

WARNING! SLIP AND FALL PRECAUTIONS

OSHA and the American Disabilities Act (ADA) have now set enforceable standards for slip resistance on pedestrian surfaces. The current coefficient of friction required by the ADA is .6 on level surfaces and .8 on ramps. DIY GARAGE FLOORS recommends the use of angular slip resistant aggregate in all coatings or resin systems that may be exposed to wet, oily or greasy conditions. It is the contractor and end users' responsibility to provide a flooring system that meets current safety standards, DIY or its sales agents will not be responsible for injury incurred in a slip and fall accident.

PROP 65 WARNING

⚠ WARNING: This product can expose you to chemicals including arsenic, which is known to the State of California to cause cancer and or birth defects. For more information, go to www.P65Warnings.ca.gov

CAUTION! PRODUCT IS EXTREMELY FLAMMABLE KEEP AWAY FROM OPEN FLAMES. KEEP OUT OF THE REACH OF CHILDREN.